

Dialogannahme

# WHEEL ALIGNMENT

Version 2025.02.19 – Prices on request



## Q.Lign 360°

Q.Lign 360° with extendable wall fixation and tablet operation for 360° space around the lift. Comes with Q.Grip wheel clamps and turntables.

**Article number: 1 690 800 012**



Ultimate productivity - vehicle after vehicle  
The Q.Lign 360° builds on the existing Q.Lign platform and focuses entirely on wheel alignment. With Q.Lign 360°, workshops raise the bar even higher to exploit their full service potential.

### Measuring at the highest level

- Camera beam measures permanently from a height of 2.8 meters
- No motor, no winch, no wear and tear
- No up, no down, no injuries or damage
- No movement, no matter if short or long wheelbases

### Everything perfectly in sight

- Four wheels, four cameras
- Separate camera for the rear axle for more accurate toe values on the front axle
- Install anywhere within 1.8 to 4,2 meters of the front axle
- Measure and adjust from 0 to 2 meters platform height at any time

### Never run out of space again

- Fixation on the wall and direct tablet operation
- No trolley, no post that take up space
- Measure from 1,8 to 4,2m distance to the front axle
- Frees up space around the complete alignment bay

### Work smarter, not harder

- Measurement starts directly with attachment of the targets to quickly determine accident vehicles
- All targets work on any wheel reduces setup times and setup errors
- Active MEMS Technology: Constant measurement against gravity for uncompromising accuracy

- Caster sweep at floor level without the need for a stool or ladder
- Access to clear and easy-to-understand PDF reports from anywhere inside your shop

### The world's first web-based wheel aligner

- Eliminates need for trolley and PC and creates more space
- Incredibly efficient with up to 95% power savings compared to PC-based systems
- Stream-to-X: Access software on any TV, PC, laptop, tablet or smartphone
- Intuitive software, streamlined operations, more productivity
- Easy integration of Q.Lign into your shop's daily processes and systems

### Full speed, without compromising on precision

- Powerful software with optimized workflow for the entire wheel alignment process
- Reduced runout process for more productivity
- 3D camera technology produces highly accurate realtime measurements

### Space requirement

- Minimum height of 2800mm
- Minimum clearance of 2800mm on four-post lifts

### Scope of delivery

- Camera beam with 4 cameras
- Q.Lign display module
- 4x Q.Grip wheel clamps
- Wall storage for Q.Grips
- 4x targets with AutoID
- Tablet
- Drive lock and steering wheel lock



## Q.Lign T.41 Kit

Q.Lign T.41 as kit version for wall mounting and tablet operation for 360° access to the lift. For customized customer solutions. Without wheel clamps and turntables.

**Article number: 1 690 800 000**



Ultimate productivity - vehicle after vehicleThe T-Series builds on the existing Q.Lign platform and focuses entirely on wheel alignment. With Q.Lign T.41, workshops raise the bar even higher and can thus exploit their full service potential.

### Measuring at the highest level

- Camera beam measures permanently from a height of 2.8 meters
- No motor, no winch, no wear and tear
- No up, no down, no injuries or damage
- No movement, no matter if short or long wheelbases

### Everything perfectly in sight

- Four wheels, four cameras
- Separate camera for the rear axle for more accurate toe values on the front axle
- Install anywhere within 1.8 to 3.3 meters of the front axle
- Measure and adjust from 0 to 2 meters platform height at any time

### Work smarter, not harder

- Measurement starts directly with attachment of the targets to quickly determine accident vehicles
- All targets work on any wheel reduces setup times and setup errors
- Active MEMS Technology: Constant measurement against gravity for uncompromising accuracy
- Caster sweep at floor level without the need for a stool or ladder
- Access to clear and easy-to-understand PDF reports from anywhere inside your shop

### The world's first web-based wheel aligner

- Eliminates need for trolley and PC and creates more space
- Incredibly efficient with up to 95% power savings compared to PC-based systems
- Stream-to-X: Access software on any TV, PC, laptop, tablet or smartphone
- Intuitive software, streamlined operations, more productivity
- Easy integration of Q.Lign into your shop's daily processes and systems

### Full speed, without compromising on precision

- Powerful software with optimized workflow for the entire wheel alignment process
- Reduced runout process for more productivity
- 3D camera technology produces highly accurate realtime measurements

### Space requirement

- Minimum height of 2800mm
- Minimum clearance of 2800mm on four-post lifts

### Scope of delivery

- Camera beam with 4 cameras
- Q.Lign display module
- 4x targets with AutoID
- Tablet
- Brake lock and steering wheel lock
- Powerbox for power supply
- Key Card 365 for international vehicle specs

Note: For the kit version, turnplates and wheel clamps must be ordered separately, depending on customer requirements.

## Q.Lign T.41 | with MultiFit wheel clamps

Q.Lign T.41 with floor mounted support column, turnplates and MultiFit wheel clamps. Operation via 27" monitor. Perfect for independent workshops and tire shops.

**Article number: 1 690 800 001**



### Ultimate productivity - vehicle after vehicle

The T-Series builds on the existing Q.Lign platform and focuses entirely on wheel alignment. With Q.Lign T.41, workshops raise the bar even higher and can thus exploit their full service potential.

### Measuring at the highest level

- Camera beam measures permanently from a height of 2.8 meters
- No motor, no winch, no wear and tear
- No up, no down, no injuries or damage
- No movement, no matter if short or long wheelbases

### Everything perfectly in sight

- Four wheels, four cameras
- Separate camera for the rear axle for more accurate toe values on the front axle
- Install anywhere within 1.8 to 3.3 meters of the front axle
- Measure and adjust from 0 to 2 meters platform height at any time

### Work smarter, not harder

- All targets work on any wheel reduces setup times and setup errors
- Active MEMS Technology: Constant measurement against gravity for uncompromising accuracy
- Caster sweep at floor level without the need for a stool or ladder
- Access to clear and easy-to-understand PDF reports from anywhere inside your shop

### The world's first web-based wheel aligner

- Eliminates need for trolley and PC and creates more space
- Incredibly efficient with up to 95% power savings compared to PC-based systems
- Stream-to-X: Access software on any TV, PC, laptop, tablet or smartphone
- Intuitive software, streamlined operations, more productivity
- Easy integration of Q.Lign into your shop's daily processes and system

### Space requirement

- Minimum height of 2800mm
- Minimum clearance of 2800mm on four-post lifts

### Scope of delivery

- Camera beam with 4 cameras
- Column with tray
- Q.Lign display module
- 4x targets with AutoID
- 27" monitor, keyboard, mouse
- Brake lock and steering wheel lock
- Front turnplates and filling pieces
- MultiFit wheel clamp (13"-22". optionally up to 27")
- Storage for MultiFit
- Key Card 365 for international vehicle specs

## Q.Lign T.41 | with Q.Grip clamps

Q.Lign T.41 with floor-mounted support column, turnplates and Q.Grip wheel clamps. Operation via 27" monitor. For wheel alignment professionals.

**Article number: 1 690 800 002**



### Ultimate productivity - vehicle after vehicle

The T-Series builds on the existing Q.Lign platform and focuses entirely on wheel alignment. With Q.Lign T.41, workshops raise the bar even higher and can thus exploit their full service potential.

### Measuring at the highest level

- Camera beam measures permanently from a height of 2.8 meters
- No motor, no winch, no wear and tear
- No up, no down, no injuries or damage
- No movement, no matter if short or long wheelbases

### Everything perfectly in sight

- Four wheels, four cameras
- Separate camera for the rear axle for more accurate toe values on the front axle
- Install anywhere within 1.8 to 3.3 meters of the front axle
- Measure and adjust from 0 to 2 meters platform height at any time

### Work smarter, not harder

- All targets work on any wheel reduces setup times and setup errors
- Active MEMS Technology: Constant measurement against gravity for uncompromising accuracy
- Caster sweep at floor level without the need for a stool or ladder
- Access to clear and easy-to-understand PDF reports from anywhere inside your shop

### The world's first web-based wheel aligner

- Eliminates need for trolley and PC and creates more space
- Incredibly efficient with up to 95% power savings compared to PC-based systems
- Stream-to-X: Access software on any TV, PC, laptop, tablet or smartphone
- Intuitive software, streamlined operations, more productivity
- Easy integration of Q.Lign into your shop's daily processes and system

### Q.Grip clamps: the last step before Touchless

- 5x faster than conventional clamps
- No removal of hubcaps
- No scratching of rims
- From 21" to 33" in under a second, no know twisting

### Space requirement

- Minimum height of 2800mm
- Minimum clearance of 2800mm on four-post lifts

### Scope of delivery

- Camera beam with 4 cameras
- Column with tray
- Q.Lign display module
- 4x targets with AutoID
- 27" monitor, keyboard, mouse
- Brake lock and steering wheel lock
- Front turnplates and filling pieces
- Q.Grip clamps (525-835mm wheel diameter)
- Storage for Q.Grips
- Key Card 365 for international vehicle specs

## Q.Lign T.41 Kit - BYOD

Q.Lign T.41 as kit version for wall mounting for 360° access to the lift. For customized customer solutions. Without Tablet, wheel clamps and turntables.

**Article number: 1 690 800 011**



Ultimate productivity - vehicle after vehicleThe T-Series builds on the existing Q.Lign platform and focuses entirely on wheel alignment. With Q.Lign T.41, workshops raise the bar even higher and can thus exploit their full service potential.

### Measuring at the highest level

- Camera beam measures permanently from a height of 2.8 meters
- No motor, no winch, no wear and tear
- No up, no down, no injuries or damage
- No movement, no matter if short or long wheelbases

### Everything perfectly in sight

- Four wheels, four cameras
- Separate camera for the rear axle for more accurate toe values on the front axle
- Install anywhere within 1.8 to 3.3 meters of the front axle
- Measure and adjust from 0 to 2 meters platform height at any time

### Work smarter, not harder

- Measurement starts directly with attachment of the targets to quickly determine accident vehicles
- All targets work on any wheel reduces setup times and setup errors
- Active MEMS Technology: Constant measurement against gravity for uncompromising accuracy
- Caster sweep at floor level without the need for a stool or ladder
- Access to clear and easy-to-understand PDF reports from anywhere inside your shop

### The world's first web-based wheel aligner

- Eliminates need for trolley and PC and creates more space
- Incredibly efficient with up to 95% power savings compared to PC-based systems
- Stream-to-X: Access software on any TV, PC, laptop, tablet or smartphone
- Intuitive software, streamlined operations, more productivity
- Easy integration of Q.Lign into your shop's daily processes and systems

### Full speed, without compromising on precision

- Powerful software with optimized workflow for the entire wheel alignment process
- Reduced runout process for more productivity
- 3D camera technology produces highly accurate realtime measurements

### Space requirement

- Minimum height of 2800mm
- Minimum clearance of 2800mm on four-post lifts

### Scope of delivery

- Camera beam with 4 cameras
- Q.Lign display module
- 4x targets with AutoID
- Powerbox for power supply
- 2x WiFi modules

Important: This version is for full customization for the customer. To complete the BYOD Kit version, the following items need to be purchased separately: control and display unit (Monitor with mouse and keyboard or Android tablet), turnplates and fillers, wheel clamps, brake and steering wheel lock.

## Q.Lign 360°

---



### Q.Lign 360°

Article number: 1 690 800 012



### Q.Lign T.41 Kit

Article number: 1 690 800 000



### Q.Lign T.41 | with MultiFit wheel clamps

Article number: 1 690 800 001



### Q.Lign T.41 | with Q.Grip clamps

Article number: 1 690 800 002



### Q.Lign T.41 Kit - BYOD

Article number: 1 690 800 011



# IMPORTANT NOTES

- Please notice: This list contains spare parts, too.
- Without instruction or assembly.
- Delivery ex works including packaging.

**VERSION 2025.02.19 – PRICES ON REQUEST**

## New Zealand Distributor

Treadway Equipped

[www.treadwayequipped.co.nz](http://www.treadwayequipped.co.nz)

0800 436 436

Order number 1 693 602 008 Print norm BB XXX / XX.XX.2020 DE · Subject to technical and program changes, errors excepted.

