



Jack for vans, 4WDs and minibuses










Rubber pad protects the lifting point.



Saddle for extra height or accessing lifting points situated behind skirts, etc.

Model	Max (Ton)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	Kg
3T-C	3	115	500	1015	170	380	925	42
4T-C	4	130	545	1270	200	465	1045	70
5T-C	5	145	560	1270	200	465	1045	71
6T-C	6	155	570	1395	210	470	1045	90
10T-C	10	165	580	1410	225	435	1045	106
12T-C	12	170	670	1700	280	470	1045	140
15T-C	15	200	600	1790	325	475	1045	162
20T-C	20	200	600	1790	325	475	1480	164



High capacity jacks 4 - 20 ton





lifting points deep under trucks.

10T-C



Additional foot pedal pumping feature provides fast saddle raising to the load.

Ergonomically designed handle for operator comfort.

Rubber coated.

system prevents unintentional lowering.

Accessories.

(Nr. 60200)

"Lift-and-turn" lowering

Accessories



Air rubber tyres fitted on point of balance enhance manoeuvrability of large jacks. Will flatten under load.

Min. height 165 mm.

Built-in safety lowering control valve for safe lowering even under maximum load.

> Large diameter swivel wheels for easy handling.

Chassis height 225 mm.



